



Panel Models :

1. KX-T918-AVL-SIP-2P
2. KX-T918-AVL-SIP-2P-Cam

Hardware :

- POE / 12Vdc.
- Full Duplex.
- IP65.
- 1 calling button + 12 – key Keypad.
- Open the door using an Access Code keypad.
- 9~24 Vdc.
- 2 relays configurable NO/NC.
- Speaker HD Audio, Includes amplifier 30 W
- Microphone HD Audio.
- Voice + Echo cancelation
- Unlimited panels per installation (each need different IP Address / Extension)
- IK07
- VPN
- Full API resful



Optional :

- 2 / 4 calling buttons.
- 2 to 8 configurable push buttons inputs (or sensors).
- 12 Key Keypad , Enter the perimeter using an access code.
- Speaker out (low impedance).
- Line out (high impedance).

Functions :

- Full Duplex
- GUI english, spanish & portuguese
- Full IP SIP device
- Register as extension of IP PBX or works standalone with direct IP Address calls
- Unicast / Multicast
- Prerecorded messages
- Access Control standalone or client
- Server: PIN, Proximity Card, Fingerprint
- Notify / HTTP commands for relays activating
- QR decoding
- Echo cancellation
- Simultaneously calls up to 5 monitors (with can call up to 100 monitors Simultaneously)

Protocol :

TCP/IP, SIP, G.711 / G.729, Opus (rcvonly), MySQL, HTTP, RTSP, RTP, FTTP, Syslog, SNTP, SNMP, DHCP

Optional addon : Camera :

- Support ONVIF/private protocol/CGI
- Sensor : Hisilicon 3516EV200 + 3MP 1/2.8" sensor (407)
DSP : 16:9 widescreen display
- Support dual stream.
Main stream: 2304×1296,1920×1080
Sub-stream : D1(704*576)/ 360P(640*360)/ CIF(352*288)
- Color Camera HD , Fish Eye