

Panel : KX-T927-4P

Panel + Camera : KX-T927-4p-Cam



Hardware :

- Full Duplex.
- IP65.
- 4 Calling Buttons.
- 9~24 Vdc. / POE
- 2 relays configurable NO/NC.
- Speaker HD Audio.
- Microphone HD Audio.
- Voice + Echo cancelation
- Unlimited panels per installation
- IK07
- Amplifier 30W



Optional :

- 2 and 4 calling buttons.
- 2 to 8 configurable push buttons inputs (or sensors)
- Speaker out (low impedance).
- Line out (high impedance).

Functions :

- Full Duplex
- GUI english, spanish & portuguese
- Full IP SIP device
- Register as extension of IP PBX or works standalone with direct IP Address calls
- Unicast / Multicast
- Prerecorded messages
- Access Control standalone or client
- Server: PIN, Proximity Card, Fingerprint
- Notify / HTTP commands for relays activating
- QR decoding
- Echo cancellation

Protocol :

TCP/IP, SIP, G.711 / G.729, Opus (rcvonly), MySQL, HTTP, RTSP, RTP, FFTP, Syslog, SNMP, SNMP, DHCP

Camera

- Support ONVIF/private protocol/CGISensor :
- Hisilicon 3516EV200 + 3MP 1/2.8" sensor (407)
- DSP : 16:9 widescreen display
- Support dual stream.
- Main stream: 2304×1296,1920×1080
- Sub-stream : D1(704*576)/ 360P(640*360)/ CIF(352*288)